




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B60N 2/28, B60R 22/10	A1	(11) International Publication Number: WO 98/25788 (43) International Publication Date: 18 June 1998 (18.06.98)
(21) International Application Number: PCT/NO97/00298 (22) International Filing Date: 11 November 1997 (11.11.97) (30) Priority Data: 965292 11 December 1996 (11.12.96) NO (71) Applicant: BEWI PRODUKTER AS [NO/NO]; N-7263 Hamarvik (NO). (72) Inventor: LÖVLIE, Kjell; Husbyveien 16F, N-7500 Stjørdal (NO). (74) Agent: CURO AS; P.O. Box 38, N-7094 Lundamo (NO).		(81) Designated States: DE, DK, FI, SE, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> <i>In English translation (filed in Norwegian).</i>

(54) Title: GUIDE FOR A SAFETY BELT AT A CHILD'S SEAT**(57) Abstract**

Guide (2) for a safety belt at a child's seat (1), intended for use in an automobile, has a fastening part (3) that is provided for fastening the belt guide (2) to the child's seat (1) and a housing (4) that is equipped with a guiding section (7) for a safety belt (6). The fastening part (3) comprises an adjustment rail (3), along which the belt guide (2) can be adjusted in the height direction. A locking wedge (15) is provided for locking the safety belt (6) relative to the guiding section (7).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

Guide for a safety-belt at a children's seat

Present invention concerns a guide for a safety-belt at a children's seat, according to the introductory part of Claim 1.

- 5 In the field of automobile safety, children are internationally classified in the following weight classes: Group 0: 0-9 kg, Group 0+: 8-13 kg, Group 1: 9-18 kg, Group 2: 15-25 kg and Group 3: 22-36 kg. The present invention is particularly directed to Group 1, Group 2 and Group 3.

There are known several different types of children's seats for automobiles. One
10 type has a built-in belt-system, the safety-belt in the automobile being used to hold the seat in place. This solution is both more time intensive and more expensive than if the safety-belt of the automobile were used both to attach the children's seat and secure the child. It is also known to use the safety-belts of the automobile in children's seats.

Today, most automobiles have lap/shoulder safety belts with automatic retraction.
15 This gives driver and passenger the freedom to move forward in the seat, if desired. However, for children in children's seats, this freedom represents a danger. In the past, children have edged forward in such a way that the lower belt has come out of its desired position over the hip and in a position over the stomach. Furthermore, the child can edge underneath the shoulder belt, thereby placing the belt over the throat,
20 etc. In a collision, this can lead to the belt cutting into the stomach region, or shoulder blade and throat, respectively, with serious injuries resulting. In children's seats it may thus be necessary to take away the freedom represented by automatic retraction, and lock the safety belt in place.

Known belt guides are, to a small degree, adjustable in line with the growth of the
25 child. Often, children's seats are intended for one weight class, and new seats must be bought when the child is growing. Up to this point in time, there are few children's seats that both take complete care of the safety of the child and are adjustable.

It is therefore an object with present invention to provide a belt guide that is lockable and can be adjusted in the height direction relative to the children's seat.

- 30 The object of the invention is achieved with a device having features as stated in the characterizing part of Claim 1. Further features are clear from the dependent claims.

In the following, the invention will be explained with reference to an example of embodiment and with reference to the enclosed drawings, where

Fig. 1 shows a side view of a children's seat having a belt guide according to present invention,

5 Fig. 2 shows a perspective view of the belt guide from Fig. 1 with the safety belt mounted,

Fig. 3 shows the belt guide from Fig. 1 in a rear view (from the seat), and

Fig. 4 shows an exploded perspective view of the belt guide from Fig. 1, in a rear view.

10

In Fig. 1 is shown a children's seat 1 of a per se known kind. At each side of the back rest is mounted a belt guide 2, where the one on the right side is shown. The belt guide comprises an adjustment rail 3 and a housing 4. The adjustment rail 3 is equipped with holes 5a, 5b on each end, for fastening to the seat by a screw or similar.

15 In Fig. 2 is shown the belt guide 2 with a safety belt 6 mounted. The housing 4 is connected to a guiding section 7, comprising a first slot 8, a second slot 9 and a lip 10. First slot 8 has an open end 11 that preferably is directed downwards. The second slot has a corresponding open end 12 that preferably also is directed downwards. The first slot 8 is somewhat wider than the second slot 9. Between the first and second slots 8,
20 9 is formed a first tongue 13. A second tongue 14 is formed on the external side of the slot 9. On the downwardly directed free end of the second tongue 14 is formed a lip 10, that is directed upwards. Preferably the lip 10 extends over a distance that is about a quarter of the width of the guiding section 7.

In the first slot 8 is situated a locking wedge 15. The locking wedge 15 comprising
25 two guiding tongues 16a, 16b that are directed against each other. The locking wedge 15 will be described in more detail below, with reference to Fig. 3 and 4.

The safety belt 6, which is the safety belt of the automobile, is threaded through the guiding section 7 as shown in Fig. 2. Firstly, it goes in the guiding tongues 16a, 16b of the locking wedge 15, then through the slot 8 on the side of the locking wedge 15,
30 behind first tongue 13, forward through the slot 9, over second tongue 14 and under the lip 10.

In Fig. 3 and 4 is shown the belt guide 2 according to the present invention, from the side that is directed in against the children's seat 1, shown in a mounted and demounted (exploded) condition, respectively.

The adjustment rail 3 is equipped with a first cogging 17 extending in the region 5 between the holes 5a, 5b. To the housing 4 is connected a tooth plate 18 having a second cogging 19 that is directed against the first cogging 17 of the adjustment rail 3. The tooth plate 18 is fixed relative to the housing 4, for example by means of screws (not shown).

In the housing 4 is situated a coil spring 20, providing a flexible fastening of the 10 house 4 to the adjustment rail 3, so that the first and second cogging 17, 18 are pressed against each other. A cover 21 is connected to the housing 4. The cover 21 has a lower end forming a stop against the first cogging 17 of the adjustment rail 3 by movement of the belt guide 2 along the adjustment rail 3. The housing 4 can thus be moved along the adjustment rail 3 by the cogging 19 being drawn away from the 15 cogging 17 of the adjustment rail.

At the upper end of the cover 21 is situated a tongue 22, extending somewhat beyond the upper end of the cover 21, and in against the center of the cover 21 by means of a surrounding groove 23. Also the cover 21 is fixed relative to the housing 4, for example by means of screws (not shown).

20 On the locking wedge 15 is situated a hole 24, in which the tongue 22 fits. In mounted condition, the locking wedge 15 will stand in the first slot 8. The tongue 22 has a certain flexibility, which makes it possible to bend to and fro. Then the locking wedge 15 can be introduced in to and retracted from, respectively, the first slot 8. When the safety belt 6 should be adjusted, the locking wedge 15 is retracted, and 25 when the adjustment is finished, the locking wedge 15 is dropped in place and the safety belt is held fast.

For larger children where it is not necessary to fasten the safety belt 6, the belt is drawn only through the slot 9.

Claims:

1. Guide (2) for a safety-belt at a children's seat (1), intended for use in an automobile, having a fastening part (3) that is provided for fastening the belt guide (2) to a children's seat (1) and a housing (4) that is equipped with a guiding section (7) for a safety belt (6),

characterized by the fastening part (3) comprises an adjustment rail (3), along which the belt guide (2) can be adjusted in height direction, and also a locking wedge (15) is provided for locking the safety belt (6) relative to the guiding section (7).

2. Guide according to Claim 1,
characterized by the adjustment rail (3) is equipped with a longitudinal cogging (17), adapted to fit with a corresponding cogging (19) on a tooth plate (18) that is fastened to the housing (4).

3. Guide according to Claim 2,
characterized by the coggings (17, 19) are mutually spring-loaded, so that they in their normal position are engaged by means of a spiral spring (20), and at adjustment can be brought out of engagement with each other by means of a force that is exerted against the effect of the spiral spring (20).

4. Guide according to any one of the previous claims,
characterized by the locking wedge (15) is equipped with two lips (16a, 16b) that are standing against each other.

5. Guide according to any one of the previous claims,
characterized by the locking wedge (15) is flexibly anchored relative to the guiding section (7), so that the safety belt (6) is released when the locking wedge (15) is drawn out and is locked when the locking wedge (15) is dropped in place.

6. Guide according to any one of the previous claims,
characterized by the locking wedge (15) has a hole (24) in which is provided a flexible tongue (22) that is a part of a cover (21) that is fastened to the housing (4).

7. Guide according to one of the previous claims,
characterized by a groove (24) is provided between the tongue (22) and the cover (21).

1/3




Fig.1

2/3




Fig. 2





Fig. 3

3/3

**Fig.4**

INTERNATIONAL SEARCH REPORT

International application No.

PCT/NO 97/00298

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: B60N 2/28, B60R 22/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: B60N, B60R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EDOC, WPIL

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 4229900 C2 (CURT WÜRSTL VERMÖGENSVERWALTUNGS GMBH & CO KG), 14 July 1994 (14.07.94), figures 1, 2, claim 1	1
A	--	2-7
X	DE 4204232 A1 (CURT WÜRSTL VERMÖGENSVERWALTUNGS GMBH & CO KG), 10 Sept 1992 (10.09.92), column 10, line 22 - column 11, line 1, figures 12,13	1
A	--	2-7
A	DE 3513220 A1 (CURT WÜRSTL VERMÖGENSVERWALTUNGS-GESELLSCHAFT MBH & CO KG), 16 October 1986 (16.10.86)	1-7
	--	

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

13 March 1998

Date of mailing of the international search report

16.03.98

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Christer Jönsson

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/NO 97/00298

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 2923125 C2 (CURT WÜRSTL VERMÖGENSVERWALTUNGS-GESELLSCHAFT MBH & CO KG), 16 December 1982 (16.12.82) --	1-7
A	EP 0251242 A2 (TORSTEN, JACOBI), 7 January 1988 (07.01.88) -- -----	1-7

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/NO 97/00298

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
DE	4229900	C2	14/07/94	NONE	
DE	4204232	A1	10/09/92	DE 9218775 U DE 9102850 U	14/09/95 29/05/91
DE	3513220	A1	16/10/86	NONE	
DE	2923125	C2	16/12/82	SE 446253 B,C SE 8004146 A	25/08/86 08/12/80
EP	0251242	A2	07/01/88	SE 0251242 T3 DE 8708863 U AU 609071 B AU 8146487 A DE 8631340 U ZA 8708757 A	10/09/87 26/04/91 26/05/88 19/02/87 18/05/88